

TRAILER T-608/2

TECHNICAL SPECIFICATIONS | EQUIPMENT



 **HOMOLOGATION
EUROPEAN**



Year of model 2022

CynkoMet[®]
Czarna Białostocka

TECHNICAL SPECIFICATIONS	
Type / Variant / Version according to EU homologation	T-2 121 11
Administrative loading capacity	~10540 kg*
Technical loading capacity	~10540 kg*
Gross vehicle weight rating.	14,000 kg
Unladen mass	3,460 kg*
Number of axles	2
Length - retracted / extended rear frame - max.	10,145 / 11,145* mm
Width	2,540 mm
Height	2,530 mm
Box type	platform
Pallet width	Yes
Extendable rear frame	Yes
DETAILED SPECIFICATIONS	
Height of floor from base	~1,200 mm
Height of ladders from floor	1,330 mm
Width of cargo box between edges	2,430 mm
Platform length	7,500 mm
Length of cargo surface, top / bottom	8,275 / 7,620 mm (+ approx. 1m max. with extended rear frame)
Loading surface	18.5 / 21* m ²
Floor sheet thickness	4 mm
Tire size	500/50-17
Track of wheels	1,900 mm
Wheelbase	5,070 mm
Drawbar coupling height - min.	335 mm
Drawbar coupling height - max.	900 mm
Transport/working speed	40 km/h
Suspension	parabolic springs
Class of cooperating tractor	58.8 kW / 80 HP

* - unladen weight and loading capacity may differ depending on the trailer's equipment

STANDARD MACHINE EQUIPMENT

Galvanized floor made of sheets, thickness 4 mm

“Y”-type drawbar with exchangeable tip, homologated according to Regulation 55 UN ECE and 167/2013*2015/208 ND

Bolted hitch tension member dia. 40

2 regulated springs supporting drawbar

Hot-dip galvanized frame (protection of the structure on the exterior and interior of profiles), stringers of the frame made of 160x160x5 and 120x60x5 closed sections

Parking handbrake with crank

Edges on side stringers of the frame, restricting movement of cargo

Holes in side stringers and handles for fastening of belts for securing cargo

Hot-galvanized ladders on the front and back of the platform, with height 1335 mm, made of closed sections

4 cords supporting ladders

Pallet width

Extendable rear frame, extending the loading surface by approx. 1m (driving on public roads with extended rear frame is prohibited)

Homologated, hot-galvanized rear bumper

Lighting installation connector cable with 7PIN 12V plug

12V lighting, homologated, rear bulb lamps, LED perimeter lighting

Homologated, double-circuit, pneumatic brake system with automatic braking force adjustment, with output for second trailer

Rear electrical and brake output to the second trailer

New 500/50-17 wheels

Axles from renowned ADR company, full beam with 90 mm square cross-section, 350x90 brake

Parabolic leaf spring suspension

Two wheel chocks placed in galvanized pockets

Wheel fenders

All of our agricultural machines are designed and tested by our design team using the latest available tools. Manufacturing is performed with the greatest diligence and in adherence to rigorous quality standards.

OPTIONAL MACHINE EQUIPMENT
Side underrun guards
Spare wheel winch with hot-galvanized wheel hanger
Central ladder stay lines
Homologated, hydraulic double-circuit brake system with automatic braking force adjustment
Full LED lighting
Hydraulic system for rear frame extension
Hydraulic quick-coupler with pressure neutralizer in hose
500/50-17 spare wheel
Surcharge for 435/50 R 19.5 wheels
435/50 R 19.5 spare wheel
Surcharge for 500/50 R17 wheels
500/50 R17 spare wheel
Manual hitch for second trailer
Warning triangle (sign distinguishing slow-moving vehicle)
Extended ladders (height from floor - 1800 mm)
90 deg. ladders
Drawbar eye 50mm
Toolbox
Water tank + soap dispenser

* it is prohibited to travel on public roads while the rear frame is extended

The data and photographs given in the catalog are for illustrative purposes only. This document and the information it contains, including prices, do not constitute a commercial offer within the meaning of art. 66 of the Civil Code. This information may be subject to change as products are continuously improved. We reserve the right to change a product's characteristics at any time. Products' specifications may change without notice. Realization of an order begins when a person from our sales department confirms the data contained in the order form.



**HOT-
GALVANIZED CONSTRUCTION**

| Agricultural trailer | T-608/2 | 10 TONS

