

# TRAILER T-104/7

TECHNICAL SPECIFICATIONS | EQUIPMENT



✓ **HOMOLOGATION  
EUROPEAN**



Year of model 2022

wersja.2.2022

**CynkoMet®**  
Czarna Białostocka

TECHNICAL SPECIFICATIONS	
Type / Variant / Version according to EU homologation	T-1 A21 71
Administrative loading capacity	~ 12,300 kg*
Technical loading capacity	~ 12,300 kg*
Gross vehicle weight rating according to PL regulations	16,000 kg
Gross vehicle weight rating according to Directive 2015/208 (only load on axles)	16,000 kg
Kerb weight (without wall extensions)	~3700 kg*
Number of axles	2
Length	6,820 mm
Width	2,550 mm
Height without extensions	~2,210 mm
Height with extensions	~2,810 mm
Box type	Side-wall, pallet type
Length of cargo box interior	4510 mm
Width of cargo box interior front/rear	2415mm
Height of box walls (without extensions)	800 mm
Height of platform from base	~1,410 mm
Floor/wall sheet thickness	5 / 2.5 mm
Loading surface	10.9 m2
Loading capacity - without extensions (with extensions)	8.7 m3 (600 extensions - 15.2 m3, 800 extensions - 17.4 m3)
Track of wheels	1,900 mm
Wheelbase	3,035 mm
Suspension	parabolic springs
Drawbar coupling height – min.	550 mm
Drawbar coupling height – max.	1,200 mm
Max. tolerable vertical load on axle	1. 8000 kg 2. 8,000 kg
Tire size	385/65 R22.5
Design speed	40 km/h
Minimum demand for tractor power	58.8 kW / 80 HP
Tipping angle of the cargo box (backward / sideways)	45 / 50
Tipping system	three-way

\* - unladen weight and loading capacity may differ depending on the trailer's equipment

All of our agricultural machines are designed and tested by our design team using the latest available tools.

Manufacturing is performed with the greatest diligence and in adherence to rigorous quality standards.

STANDARD MACHINE EQUIPMENT
Wall height 800 mm with thickness 2.5 mm, hot-galvanized
Central bolt-locking of walls (bottom sideboards)
Exterior ladder and steps inside cargo box - hot-galvanized - with anti-skid steps facilitating access to cargo box
Maintenance support of cargo box, hot-galvanized
"Y"-type drawbar with exchangeable tip, homologated according to Regulation 55 UN ECE and 167/2013*2015/208 ND
Bolted hitch tension member dia. 40
Hot-galvanized frame of cargo box
Main stringers (with variable cross-section) of cargo box frame made of bent high-strength sheets
Galvanized cargo box floor welded out of two sheets with a thickness of 5 mm, bolted and riveted
Hot-dip galvanized bottom frame (protection of the structure on the exterior and interior of profiles), stringers of the frame made of 200x80x6 and 160x80x6 closed sections
Parking handbrake with crank
Grain chute, hot-galvanized, with blockade in the rear wall
2 regulated springs supporting drawbar
Homologated, hot-galvanized bumper
Side wall tensioning flat bars
Pallet width
Tipping installation protected against excessive box inclination by cut-off valve
Lighting installation connector cable with 7PIN 12V plug
12V lighting, homologated, rear bulb lamps, LED perimeter lighting
Hydraulic tipping installation of cargo box made of galvanized steel tubes and flexible hoses
Hydraulic connectors to tractor, type ISO 7241-1 DN 12.5
Homologated, double-circuit, pneumatic brake system with automatic braking force adjustment, with output for second trailer.
Rear hydraulic, electrical and brake output to the second trailer
New 385/65 R22.5 wheels
Axles from renowned ADR company, full beam with 90 mm square cross-section, 406 x 120 brake
Parabolic leaf spring suspension
Two wheel chocks placed in galvanized pockets
Telescopic actuator with articulated suspensions, four-level with 1700 mm pitch. Useful force at fourth level with diameter 120 mm, at nominal pressure 16 MPa = 180 kN (~18.3T)
Wheel fenders

OPTIONAL MACHINE EQUIPMENT
Spare wheel winch with hot-galvanized wheel hanger**
Hot-galvanized tarpaulin frame made of 40x40x3 closed profiles
Hot-galvanized 600 mm wall extensions, thickness 2.5 mm
Hot-galvanized 800 mm wall extensions, thickness 2.5 mm
Chute for precise tipping, hot-galvanized
Hot-galvanized work platform
Full LED lighting
Homologated, hydraulic double-circuit brake system with automatic braking force adjustment
Surcharge for "new" 400/60 22.5 wheels
400/60 22.5 "new" spare wheel
385/65 R22.5 "new" spare wheel
Roll-up tarpaulin
Hydraulic quick-coupler with pressure neutralizer in hose
Warning triangle (sign distinguishing slow-moving vehicle)
DUPLEX - painted set of walls
DUPLEX - painted set of extensions
Drawbar eye 50mm
Set of side (bicycle) guards
Automatic hitch for second trailer
Manual hitch for second trailer
Water tank + soap dispenser**
Toolbox**

\*\* - in the case of installation of the spare wheel winch with the wheel hanger, it is not possible to install the water tank with soap dispenser and toolbox

The data and photographs given in the catalog are for illustrative purposes only. This document and the information it contains, including prices, do not constitute a commercial offer within the meaning of art. 66 of the Civil Code. This information may be subject to change as products are continuously improved. The manufacturer reserves the right to change a product's characteristics at any time. Products' specifications may change without notice.



HOT-  
GALVANIZED CONSTRUCTION

**CynkoMet®**  
Czarna Białostocka

