

TRAILER PW-22

TECHNICAL SPECIFICATIONS | EQUIPMENT

**Specialist trailer
for root vegetables**



Year of model 2023





CynkoMet[®]
Czarna Białostocka

TECHNICAL SPECIFICATIONS	
Type/version/variant	S2a/PW22
Technically (design) permissible total weight rating	27 800 kg
Gross vehicle weight rating	22 000 kg
Including axle max.	18 000 kg
Including a drawbar max. (K80 hook)	4 000 kg
Load capacity	19 100 kg
Unladen mass	8 700 kg
Tire size	600/50 R22,5 159 D
Track of wheels	2130 mm
Height of floor above ground	1403 mm
Length	9 017 mm
Width - folded	2 730 mm
Width - unfolded	3 957 mm
Height - folded	2 676 mm
Height - unfolded	3 213 mm
Hitch height (adjustable)	550-750 mm
Recommended size of the box (GxSxW)	1600 x 1200 x 1200-1250mm
Number of boxes	8
Dimensions of one frame for boxes (width x length)	1200 mm x 6652 mm
Transport speed	40 km/h
Suspension	Parabolic springs in the system tandem with a stabilizer

* - own mass and load capacity may vary depending on the equipment of the trailer

STANDARD EQUIPMENT
Palette frames hydraulically tilted by 45°
Hydraulically lifted pallets blocking frames
Frames secured with a foam shock absorbers protected with a tarpaulin to prevent vegetables to bother when wearing a combine from the elevator
Source for crates secured with rubber aprons against vegetables
All -galvanized structure
Cushioned and positioning with hydraulic cylinders with two batteries
Firewood galvanized drawbar with a replaceable K80 hook, approval drawn in accordance with the Regulations of the UN 55 (Reg. 55 UN ECE)
Hydraulic support
Axes with a technical load capacity of 14,000 kg / axis
New tires - size 600/50R 22.5 159 D
Mechanical parking brake with a crank
Lighting installation connection cable with 7pin 12V plug
12V lighting, approved
Two-wire pneumatic brake installation with an automatic braking force regulator
Hydraulic connection for the ISO 7241-1 DN 12.5 tractor
Hydraulics cable control pilot

The owner of the design of the machine in question is Cynkomet Sp. z o.o. And as such, he reserves the right to make modifications and structural changes in the product after informing the contracting authority in the event if these changes affect the product's utility parameters.



The data and photographs given in the catalog are for illustrative purposes only. This document and the information it contains, including prices, do not constitute a commercial offer within the meaning of art. 66 of the Civil Code. This information may be subject to change as products are continuously improved. The manufacturer reserves the right to change a product's characteristics at any time. Products' specifications may change without notice.



HOT DIP GALVANIZED CONSTRUCTION