

# TRAILER T-608/3L with side guards

TECHNICAL SPECIFICATIONS | EQUIPMENT



✓ **HOMOLOGATION  
EUROPEAN**



Year of model 2022

**CynkoMet®**  
Czarna Białostocka

| TECHNICAL SPECIFICATIONS                              |  |
|---|--|
| Type / Variant / Version according to EU homologation | T-2 531 11                                 |
| Administrative loading capacity                       | ~13460 kg*                                 |
| Technical loading capacity                            | ~13460 kg*                                 |
| Gross vehicle weight rating                           | 19,000 kg                                  |
| Unladen mass  | 5,540 kg*                                  |
| Number of axles                                       | 3  |
| Length - retracted / extended rear frame - max.       | 11,740 / -- mm                             |
| Width   | ~2,480 mm                                  |
| Height  | 2,630 mm                                   |
| Box type  | platform                                   |
| Pallet width  | Yes  |
| Extendable rear frame                                 | No   |
| DETAILED SPECIFICATIONS                               |  |
| Height of floor from base                             | ~1,200 mm                                  |
| Height of ladders from floor                          | Front and rear - 2,375 mm, sides ~2,225 mm |
| Width of cargo box between edges                      | 2,430 mm                                   |
| Platform length                                       | 9,300 mm                                   |
| Length of cargo surface, top / bottom                 | 9,310 mm                                   |
| Loading surface                                       | 22.6m <sup>2</sup>                         |
| Floor sheet thickness                                 | 4 mm                                       |
| Tire size   | 500/50-17                                  |
| Track of wheels                                       | 1,900 mm                                   |
| Wheelbase   | 1-2. 4,875mm, 2-3. 1,220 mm                |
| Drawbar coupling height – min.                        | 335 mm                                     |
| Drawbar coupling height – max.                        | 900 mm                                     |
| Transport/working speed                               | 40 km/h                                    |
| Suspension  | parabolic springs                          |
| Class of cooperating tractor                          | 73.6 kW / 100 HP                           |

\* - unladen weight and loading capacity may differ depending on the trailer's equipment

| <b>STANDARD MACHINE EQUIPMENT</b>  |  |
|--|--|
| Galvanized floor made of sheets, thickness 4 mm  |  |
| "Y"-type drawbar with exchangeable tip, homologated according to Regulation 55 UN ECE and 167/2013*2015/208 ND   |  |
| Bolted hitch tension member dia. 40  |  |
| 2 regulated springs supporting drawbar   |  |
| Hot-dip galvanized frame (protection of the structure on the exterior and interior of profiles), stringers of the frame made of 160x160x5 and 120x60x5 closed sections |  |
| Parking handbrake with crank   |  |
| Edges on side stringers of the frame, restricting movement of cargo  |  |
| Holes in side stringers and handles for fastening of belts for securing cargo  |  |
| Hydraulic side guards for securing cargo - one- or two-sided   |  |
| Pallet width   |  |
| Homologated, hot-galvanized rear bumper  |  |
| Lighting installation connector cable with 7PIN 12V plug   |  |
| 12V lighting, homologated, rear bulb lamps, LED perimeter lighting   |  |
| Homologated, double-circuit, pneumatic brake system with automatic braking force adjustment, with output for second trailer  |  |
| Rear electrical and brake output to the second trailer   |  |
| New 500/50-17 wheels   |  |
| Axles from renowned ADR company, full beam with 90 mm square cross-section, 350x90 brake   |  |
| Parabolic leaf spring suspension   |  |
| Two wheel chocks placed in galvanized pockets  |  |
| Wheel fenders on last axle   |  |

*All of our agricultural machines are designed and tested by our design team using the latest available tools.  
Manufacturing is performed with the greatest diligence and in adherence to rigorous quality standards.*

| <b>OPTIONAL MACHINE EQUIPMENT</b>  |  |
|--|--|
| Side underrun guards   |  |
| Spare wheel winch with hot-galvanized wheel hanger   |  |
| Homologated, hydraulic double-circuit brake system with automatic braking force adjustment |  |
| Full LED lighting  |  |
| Hydraulic quick-coupler with pressure neutralizer in hose                                  |  |
| 500/50-17 spare wheel  |  |
| Surcharge for 435/50 R 19.5 wheels   |  |
| 435/50 R 19.5 spare wheel  |  |
| Surcharge for 500/50 R17 wheels  |  |
| 500/50 R17 spare wheel   |  |
| Manual hitch for second trailer  |  |
| Warning triangle (sign distinguishing slow-moving vehicle)                                 |  |
| Drawbar eye 50mm   |  |
| Toolbox  |  |
| Water tank + soap dispenser  |  |
| 1/4 mudguards on front axle  |  |

The data and photographs given in the catalog are for illustrative purposes only. This document and the information it contains, including prices, do not constitute a commercial offer within the meaning of art. 66 of the Civil Code. This information may be subject to change as products are continuously improved. We reserve the right to change a product's characteristics at any time. Products' specifications may change without notice. Realization of an order begins when a person from our sales department confirms the data contained in the order form.





| Agricultural trailer T-608/3L with side guards | 14 TONS

